



Description

Tork OptiServe® Coreless is a high-capacity toilet paper system for facilities where efficiency, sustainability and providing a great experience are key. It´s a better alternative than conventional toilet paper and traditional jumbo rolls. The wide offer of dispensers means different needs within a facility can be met with only one type of toilet paper.

- Perforated 2-ply coreless toilet paper with attractive design
- 3x more paper compared to conventional rolls to avoid run-outs
- Compact rolls: refill less often and save time
- No core and no wrap means less waste
- Half the storage space vs conventional toilet rolls
- Tork Easy Handling® packaging for ergonomic carrying

Certifications



Product Details

System	T7
Color	White
Length per case	2,263.2 m
Embossing	Yes
Number of Sheets	820
Total Grammage	33 g
Print	No
Roll diameter	13.1 cm
Roll length	94.3 m
Sheet length	11.5 cm
Pulp Quality Indicator	2
Ply	2
Roll width	9.3 cm
Roll/Piece Net Weight	289.41 g
Roll Gross Weight	289.41 g
Fibre Type	Recycled

Shipping Data

	Consumer Units (CON)	Transport unit (TRP)	Pallet (PAL)
EAN	7322542403815	7322542403839	7322542403846
Packaging Material	none	Plastic Shrink Film	-
Pieces	1	24 (24 CON)	720 (30 TRP)
Height	93 mm	186 mm	1,277 mm
Length	131 mm	524 mm	1,200 mm
Width	131 mm	393 mm	1,000 mm
Gross Weight	289.41 g	6.99 kg	209.76 kg
Net Weight	289.41 g	6.95 kg	208.37 kg
Volume	1.6 dm3	38.3 dm3	1.15 m3
Layers Per Pallet	-	-	6
TRP Per Layer	-	-	5

Compatible Products



TORK OPTISERVE CORELESS 2-ROLL DIS WHI
558041



Tork OptiServe Coreless 2-Roll Dis Black
558042



TORK OPTISERVE CORELESS 4-ROLL DIS WHI
558051



Tork OptiServe Coreless 4-Roll Dis Black
558052

Environmental Information

Content

The product is made from

Recycled fibres
Chemicals

The packaging material is made from paper or plastic.

Material

Recycled fibres

Recycling of paper is an efficient use of resources as the wood fibres are used more than once.

High demands are put on quality and purity of recovered paper, considering each step of the chain (collecting, sorting, transporting, storage, use), to ensure safe and hygienic products.

Recycled fibres can be produced from different types of recovered paper, such as collected newsprint, magazines, office waste, paper cups, drink cartons, corrugated boxes and paper hand towels. The choice of recovered paper grades is made for each product, depending on its specific requirements on performance properties and brightness. The paper is dissolved in water, washed and treated with chemicals under high temperature and screened to separate out impurities.

Bleaching of pulp, used for tissue, is primarily a process to remove substances that could have a negative effect on important properties of the finished product such as purity, absorption, strength and colour of the pulp.

Bleaching of the recycled fibre pulp is done using chlorine-free bleaching agents (hydrogen peroxide and sodium dithionite). Some of our products are bleached and some are not.

For bleached products we use bleaching agents (to increase the brightness of pulp from recovered paper).

Chemicals

All chemicals (process aids as well as additives) are assessed from an environmental, occupational health and safety and product safety point of view.

To control product performance we use additives:

- Wet strength agents (for Wipers and Hand Towels)
- Dry strength agents (are used together with mechanical treatment of the pulp to make strong products like wipers)
- For coloured papers dyes and fixatives (to secure perfect fastness of the colour) are added
- For printed products printing inks (pigments with carriers and fixatives) are applied
- For multi ply products we often use water soluble glue to secure the integrity of the product

In most of our mills we do not add optical brighteners but it often occurs in recovered paper since it is used in printing paper.

We do not use softeners for professional hygiene products.

High product quality is secured through quality and hygiene management systems throughout production, storage and transport.

In order to maintain a stable process and product quality the paper manufacturing process is supported by the following chemicals/ process aids:

- defoamers (surfactants and dispersing agents)
- pH-control (sodium hydroxide and sulphuric acid)
- retention aids (chemicals that help to agglomerate small fibres to prevent fibre loss)
- Coating chemicals (that help to control the creping of the paper to make it soft and absorbent)

To reuse broke and to utilise recovered fibres we use:

- Pulping aid (chemicals that help to repulp wet strong paper)
- Flocculation chemicals (that help to clean out printing inks and fillers from recovered paper)
- Bleaching agents (to increase the brightness of pulp from recovered paper)

In the cleaning of our waste water we use flocculation agents and nutrients for the biological treatment to secure that no negative impact on water quality comes from our mills.

Environmental certification	This product is certified with the EU Ecolabel with certificate number SE/004/001. This product is certified for FSC® with certificate number SA-COC-08266.
Packaging	Fulfilment of Packaging and Packaging Waste Directive (94/62/EC): Yes
Article creation date and latest article revision	Date of issue: 03-07-2024 Revision date: 13-07-2026
Production	This product is produced at Hondouville - FR mill and certified according to ISO 9001, ISO 14001 (Environmental management systems), BRC-IoP, ISO 45001, ISO 50001 and FSC Chain-Of-Custody.
Destruction	This product is suitable to be taken care of in the normal sewage system of the community.

Essity UK Ltd, Southfields Road, Dunstable, Bedfordshire LU6 3EJ, United Kingdom